











11	Washer	1PCS	Iron	Ni
10	Nut	1PCS	Brass	Ni
9	Corer board	1PCS	PC	Transparent
8	Basis	1PCS	PA	Black
7	Spring	2PCS	Carbon steed Ø0.3	Tin
6	Shaft sleeve	1PCS	Brass	Ni
5	Fixed pin	1PCS	H65 t=0.35	Silver
4	Fixed pin	1PCS	H65 t=0.35	Silver
3	Contact pin	1PCS	H65 t=0.25	Silver
2	Contact pin	1PCS	H65 t=0.25	Silver
1	Ground pin	1PCS	H65 t=0.4	Silver
Part number	Description		Material	Plating

SPECIFICATION

1. Rating : -40~55℃, DC 30V 0.5A;
2. Contact resistance: ≤30mΩ;
3. Insulation resistance: ≥100MΩ (DC250V);
4. Withstand voltage: 500V AC (50Hz)/min;
5. Insertion and extraction force: 3-20N;
6. life test: 5,000 cycles.



GENERAL TOLERANCE			
X	±0.30	X°	±2.0°
.X	±0.20	X°	±1.0°
.XX	±0.10	.XX°	±0.5°

Unit: mm

TOLERANCE: UNLESS OTHERWISE SPECIFIED		
UNDER 1.5±0.05	1.5~10±0.1	OVER 10±0.2

All material in accordance with RoHS + REACH!

3,5 mm stereo socket, with switch, 90° for PCB mounting

Ledino Deutschland GmbH
the energy saving company

Ledino Deutschland GmbH
Albert-Einstein-Ring 27
D-14532 Berlin/Kleinmachnow

Tel. +49 (0)30 80540 96 / 98
Fax +49 (0)30 8055317
Email: info@ledino.de

Prep.:	Date:	Rev.	Date:	Remark:	Prep.:	Check.:
J.A.	15.05.15					
Check.:	Date:					
Approv.:						

Item No.: **KB 3 SF**

Customer Item No.:

EAN Bar Code:

All rights reserved

PRS